

LED Cylinder Lighting



LIJIACHENG
Electric



LED Cylinder Lighting Single Side Wall Mount




FEATURES

- Die-cast aluminum housing with durable paint finish
- Plastic optical lens is protected by gasket tempered glass clear cover
- Aluminum extruded heat sink designed to facilitate heat dissipation to reduce LED junction temperature for maintaining lighting output and life span of the LED
- 100-277V input, 50/60Hz - PF >0.9 - CRI >90
- 3 Lunmen output selectable
- Available in wide range of color temperature from 2700K-5000K
- Different beam angle of optical lens options
- Photocell provides automatic on/off for optional
- Ambient temperature: -20°C to 45°C
- 5 years limited warranty
- ETL listed for WET location usage

Finish

BK		Black
WH		White
BZ		Bronze
SN		Satin Nickel

Beam angle



Item Number	Watts	Lumens	Efficacy(lm/W)	Dimmable	Life Span(Hr)	Diameter(Inch)	Height(Inch)	Weight(Lb)
HT-WMSD418WIV-XXCNJ	18	1260	70	D / N	50000	4.48	6.22	3.75
HT-WMSD425WIV-XXCNJ	25	1750	70	D / N	50000	4.48	6.22	3.75
HT-WMSD525WIV-XXCNJ	25	1750	70	D / N	50000	4.88	7.64	4.54
HT-WMSD536WIV-XXCNJ	36	2520	70	D / N	50000	4.88	7.64	4.54
HT-WMSD636WIV-XXCNJ	36	2520	70	D / N	50000	6.22	10.39	6.62
HT-WMSD643WIV-XXCNJ	43	3010	70	D / N	50000	6.22	10.39	6.62
HT-WMSD843WIV-XXCNJ	43	3010	70	D / N	50000	8.00	12.78	9.68
HT-WMSD854WIV-XXCNJ	54	3920	70	D / N	50000	8.00	12.78	9.68
HT-WM3SD422D/UNV-XX82-V#	14/18/22	1200/1600/1900	85	D / N	50000	3.76	7.64	3.64
HT-WM3SD435D/UNV-XX82-V#	25/30/35	2300/2800/3300	92	D / N	50000	3.76	7.64	3.64

LED Cylinder Lighting Pendant Mount

FEATURES

- Die-cast aluminum housing with durable paint finish
- Plastic optical lens is protected by gasket tempered glass clear cover
- Aluminum extruded heat sink designed to facilitate heat dissipation to reduce LED junction temperature for maintaining lighting output and life span of the LED
- 100-277V input, 50/60Hz - PF >0.9 - CRI >90
- Pendant mount, with swivel canopy suspension kit
- Available in wide range of color temperature from 2700K-5000K
- Different beam angle of optical lens options
- Photocell provides automatic on/off for optional
- Ambient temperature: -20°C to 45°C
- 5 years limited warranty
- ETL listed for WET location usage

Finish

BK
Black



WH
White




BZ
Bronze





SN
Satin Nickel



Beam angle



Mounting accessories



Swivel Canopy
Suspension Kit

2 x 12in
Extension Rod

Item Number	Watts	Lumens	Efficacy(lm/W)	Dimmable	Life Span(Hr)	Diameter(Inch)	Height(Inch)	Weight(Lb)
HT-PMD418WIV-XXCNJ	18	1260	70	D / N	50000	4.48	6.18	2.43
HT-PMD425WIV-XXCNJ	25	1750	70	D / N	50000	4.48	6.18	2.43
HT-PMD525WIV-XXCNJ	25	1750	70	D / N	50000	4.88	7.64	3.09
HT-PMD536WIV-XXCNJ	36	2520	70	D / N	50000	4.88	7.64	3.09
HT-PMD636WIV-XXCNJ	36	2520	70	D / N	50000	6.22	9.09	4.85
HT-PMD643WIV-XXCNJ	43	3010	70	D / N	50000	6.22	9.09	4.85
HT-PMD843WIV-XXCNJ	43	3010	70	D / N	50000	8.00	10.39	8.16
HT-PMD854WIV-XXCNJ	54	3920	70	D / N	50000	8.00	10.39	8.16

LED Cylinder Lighting Ceiling Mount



FEATURES


- Die-cast aluminum housing with durable paint finish
- Plastic optical lens is protected by gasket tempered glass clear cover
- Aluminum extruded heat sink designed to facilitate heat dissipation to reduce LED junction temperature for maintaining lighting output and life span of the LED
- 100-277V input, 50/60Hz - PF >0.9 - CRI >80
- Surface mount, 3 key hole fixing points in the intallation plate directly to the ceiling
- Available in wide range of color temperature from 2700K-5000K
- Different beam angle of optical lens options
- Photocell provides automatic on/off for optional
- Ambient temperature: -20°C to 45°C
- 5 years limited warranty
- ETL listed for WET location usage



Finish

BK		Black
WH		White
BZ		Bronze
SN		Satin Nickel

Beam angle



Item Number	Watts	Lumens	Efficacy(lm/W)	Dimmable	Life Span(Hr)	Diameter(Inch)	Height(Inch)	Weight(Lb)
HT-SMD418WIV-XXCNJ	18	1260	70	D / N	50000	4.48	6.93	2.65
HT-SMD425WIV-XXCNJ	25	1750	70	D / N	50000	4.48	6.93	2.65
HT-SMD525WIV-XXCNJ	25	1750	70	D / N	50000	4.88	8.23	3.31
HT-SMD536WIV-XXCNJ	36	2520	70	D / N	50000	4.88	8.23	3.31
HT-SMD636WIV-XXCNJ	36	2520	70	D / N	50000	6.22	9.88	5.51
HT-SMD643WIV-XXCNJ	43	3010	70	D / N	50000	6.22	9.88	5.51
HT-SMD843WIV-XXCNJ	43	3010	70	D / N	50000	8.00	11.14	9.26
HT-SMD854WIV-XXCNJ	54	3920	70	D / N	50000	8.00	11.14	9.26

LED Cylinder Lighting Up&Down light Wall Mount

Finish


BK  Black

WH  White

BZ  Bronze

SN  Satin Nickel

Beam angle



FEATURES

- Die-cast aluminum housing with durable paint finish
- Plastic optical lens is protected by gasket tempered glass clear cover
- Aluminum extruded heat sink designed to facilitate heat dissipation to reduce LED junction temperature for maintaining lighting output and life span of the LED
- 100-277 input, 50/60Hz - PF >0.9 - CRI >90
- Light radiates from top and bottom of cylinder
- 3 Lunmen output selectable
- Available in wide range of color temperature from 2700K-5000K
- Different beam angle of optical lens options
- Photocell provides automatic on/off for optional
- Ambient temperature: -20°C to 45°C
- 5 years limited warranty
- ETL listed for WET location usage

Item Number	Watts	Lumens	Efficacy(lm/W)	Dimmable	Life Span(Hr)	Diameter(Inch)	Height(Inch)	Weight(Lb)
HT-WMDD418WIV-XXCNJ	18	1260	70	D / N	50000	4.48	6.34	3.75
HT-WMDD425WIV-XXCNJ	25	1750	70	D / N	50000	4.48	6.34	3.75
HT-WMDD525WIV-XXCNJ	25	1750	70	D / N	50000	4.88	6.97	4.41
HT-WMDD536WIV-XXCNJ	36	2520	70	D / N	50000	4.88	6.97	4.41
HT-WMDD636WIV-XXCNJ	36	2520	70	D / N	50000	6.22	7.72	7.05
HT-WMDD643WIV-XXCNJ	43	3010	70	D / N	50000	6.22	7.72	7.05
HT-WMDD843WIV-XXCNJ	43	3010	70	D / N	50000	8.00	10.08	11.46
HT-WMDD854WIV-XXCNJ	54	3290	70	D / N	50000	8.00	10.08	11.46
HT-WM3SS422D/UNV-XX82-V#	14/18/22	1200/1600/1900	85	D / N	50000	3.76	7.64	3.64
HT-WM3SS435D/UNV-XX82-V#	25/30/35	2300/2800/3300	92	D / N	50000	3.76	7.64	3.64



5 Years
Limited Warranty



120-277V
Universal Voltage



Wet Location



LIJIACHENG
Electric

Hangzhou Lijiacheng Electric Co., Ltd
GaoHong Industrial Park, Lin'an City, ZheJiang China 311307
Tel: +86 571-6110 5667
Fax: +86 571-6110 5663
E-mail: chris@ljclight.com

www.ljclight.cn

